

## DESCALCIFICADORES GAMA DOMESTICA



MODELO	RESINA LTS	Q-MAX M3/h	Capacidad de intercambio (°hfxm3)		
			45 gr.	90 gr.	250 gr.
Robosoft rbs-14/ED	14	1,9	40	67	109
Robosoft rbs-17/ED	17	1,9	47	80	130
Robosoft rbs-24/ED	24	2,3	71	120	195



MODELO	RESINA LTS	Q-MAX M3/h	C.SAL KG	CICLO ENTREREGENERACIONES		
				30°HF	50°HF	70°HF
KAPPA-700/008/V	8	0,8	0,9	1,00	0,60	0,43
KAPPA-700/012/V	12	1,0	1,6	2,15	1,30	0,90
KAPPA-700/018/V	18	1,5	2,4	3,20	1,90	1,35
KAPPA-700/025/V	25	2,0	3,4	4,40	2,65	1,90



MODELO	RESINA LTS	Q-MAX M3/h	C.SAL KG	CICLO ENTREREGENERACIONES		
				30°HF	50°HF	70°HF
SNT10/700/016/V	16	1,2	2,0	2,67	1,60	1,14
SNT10/700/020/V	20	1,6	3,2	4,00	2,40	1,71
SNT10/700/030/V	30	2,4	4,1	5,33	3,2	2,29



MODELO	RESINA LTS	Q-MAX M3/h	C.SAL KG	CICLO ENTREREGENERACIONES		
				30°HF	50°HF	70°HF
DUO5600/015/V	15	1,2	3,0	3,00	1,80	1,29
DUO5600/020/V	20	1,6	4,0	4,00	2,40	1,71
DUO5600/030/V	30	2,4	6,0	6,00	3,60	2,57
DUO5600/045/V	45	2,8	9,0	9,00	5,40	3,86
DUO5600/070/V	70	3,0	14,0	14,00	8,40	6,00
DUO5600/100/V	100	4,0	20,0	20,00	12,00	8,57
DUO5600/125/V	125	4,4	25,0	25,00	15,00	10,71